



MATERIAL SAFETY DATA SHEET
100% SYNTHETIC 2-STROKE MOTOR OIL
MOTORCYCLE / SNOWMOBILE / OUTBOARD MOTOR / ENGINE

Page 1 of 7

MSDS Number: 12020

Revision Date: 8/09/2010

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: TEXAS TEA 100% SYNTHETIC 2-STROKE MOTOR / OUTBOARD MOTOR / ENGINE / MOTORCYCLE / SNOWMOBILE

Product Use: NA

Synonyms: NA

Manufacturer:

TEXAS TEA LUBES
425 N. Lake Blvd.#7/PO Box 1911
Tahoe City, CA 96145 U.S.A.

Contact Information:

Medical Emergency: Dial 911
Transportation Emergency Response
(Emergency spill information):
CHEMTREC (USA): (800) 424 9300
Internet Address:TEXASTEALUBES.com

2. COMPONENT INFORMATION

Component	CAS No.	Weight Percent Range	Hazardous in Blend
HIGHLY HYDROTREATED PARAFFINIC BASE OILS	64741-89-5 64742-54-7 64742-55-8	80 - 95	No
PAO SYNTHETIC BASE OILS	68037-01-04 68037-01-04 68649-12-7 163149-29-9 151006-63-2 151006-62-1 151006-60-9		
ESTER SYNTHETIC BASE STOCKS	27178-16-1 16958-92-2		
POLYBUTENE	9003-29-6	< 10	No
NAPHTHALENE	91-20-3	< 0.5	No
DIPHENYLAMINE	122-39-4	< 1	No

This product is NOT HAZARDOUS according to OSHA 29 CFR 1910.1200.



MATERIAL SAFETY DATA SHEET

100% SYNTHETIC 2-STROKE MOTOR OIL

MOTORCYCLE / SNOWMOBILE / OUTBOARD MOTOR / ENGINE

Page 2 of 7

3. HAZARDS IDENTIFICATION

IMMEDIATE HEALTH EFFECTS

EYE: Not expected to cause prolonged or significant eye irritation.

SKIN: Contact with the skin is not expected to cause prolonged or significant irritation. Not expected to be harmful to internal organs if absorbed through the skin.

INGESTION: Not expected to be harmful if swallowed.

INHALATION: This product is not expected to pose an inhalation hazard under conditions of normal use. This product has a low vapor pressure and is not expected to present an inhalation hazard at ambient conditions. Caution should be taken to prevent aerosolization or misting of this product. Acute and chronic overexposures generated under unusual conditions may be irritating to the respiratory tract.

4. FIRST AID INFORMATION

Eye Contact: Immediately flush eyes with large amounts of water and continue flushing until irritation subsides. If material is hot, treat for thermal burns and seek immediate medical attention.

Skin Contact: No treatment is necessary under ordinary circumstances. Remove contaminated clothing. Wash contaminated area thoroughly with soap and water. If material is hot, submerge injured area in cold water. If victim is severely burned, remove to a hospital immediately.

Inhalation: This material has a low vapor pressure and is not expected to present an inhalation exposure at ambient conditions. If vapor or mist is generated when the material is heated, and the victim experiences signs of respiratory tract irritation, remove to fresh air.

Ingestion: No treatment is necessary under ordinary circumstances. Do not induce vomiting. This material does not present any known ingestion hazard.

5. FIRE AND EXPLOSION INFORMATION

Flammable Properties

Flash Point: > 212 °F, > 100 °C

Test Method: ASTM D 92 (C.O.C.)

Flammable Limits in Air

Upper Percent: NA

Lower Percent: NA

Auto-ignition Temperature: NA

Test Method: NA

NFPA Ratings: Health: 1 Flammability: 1 Reactivity: 0

Extinguishing Media: Use dry chemical, foam, or carbon dioxide.

Fire Fighting Measures

Special Fire Fighting Procedures and Equipment: Water may be ineffective but can be used to cool containers exposed to heat or flame to prevent vapor pressure buildup and possible container rupture. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid.



MATERIAL SAFETY DATA SHEET
100% SYNTHETIC 2-STROKE MOTOR OIL
MOTORCYCLE / SNOWMOBILE / OUTBOARD MOTOR / ENGINE

Page 3 of 7

Unusual Fire and Explosion Conditions: Dense smoke may be generated while burning. Carbon monoxide, carbon dioxide, and other oxides may be generated as products of combustion.

Hazardous Combustion By-Products: None

6. ACCIDENTAL RELEASE MEASURES

Emergency Number: (800) 424 9300

Protective Measures: Eliminate all sources of ignition in vicinity of spilled material.

Accidental Release Measures: Stop the source of the leak or release. Clean up releases as soon as possible, observing precautions in Exposure Controls/Personal Protection. Contain liquid to prevent further contamination of soil, surface water or ground-water. Clean up small spills using appropriate techniques such as sorbent materials or pumping. Where feasible and appropriate, remove contaminated soil.

Reporting: Follow prescribed procedures for reporting and responding to larger releases. Report spills to local authorities and/or the U.S. Coast Guard's National Response Center at (800) 424-8802 as appropriate or required.

7. HANDLING AND STORAGE INFORMATION

Handling: Fire extinguishers should be kept readily available. See NFPA 30 and OSHA 1910.106 – Flammable and Combustible Liquids.

Storage: Do not transfer to unmarked containers. Store in closed containers away from heat, sparks, open flame, or oxidizing materials. See also additional information section below.

Empty Container Warnings

Drums: Empty drums should be completely drained, properly bunged and promptly returned to a reconditioned drum, or properly disposed. Empty containers retain product residue and can be dangerous.

Plastic: Do not reuse this container. Empty container may retain product residues.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits and Guidelines: This product does not contain any components with OSHA or ACGIH exposure limits.

Personal Protective Equipment

Eye/Face Protection: No special eye protection is normally required. Where splashing is possible, wear safety glasses with side shields as good safety practice.

Skin Protection: No skin protection is required for single, short duration exposures. For prolonged or repeated exposures, use impervious clothing (boots, gloves, aprons, etc..) over parts of the body subject to exposure. If handling hot material, use insulated protective clothing (boots, gloves, aprons, etc.). Launder soiled clothes. Properly dispose of contaminated leather articles including shoes, which cannot be decontaminated.

Respiratory Protection: Respiratory protection is not required under conditions of normal use. If vapor or mist is generated when the material is heated or handle, use an organic vapor respirator with a dust and mist filter. All respirators must be NIOSH certified. Do not use compressed oxygen in hydrocarbon atmospheres.



MATERIAL SAFETY DATA SHEET

100% SYNTHETIC 2-STROKE MOTOR OIL

MOTORCYCLE / SNOWMOBILE / OUTBOARD MOTOR / ENGINE

Page 4 of 7

Personal Hygiene: Always wash hands and face with soap and water before eating, drinking, or smoking. Consumption of food and beverage should be avoided in work areas where this product is present.

Engineering Control/Work Practices: Use in a well-ventilated area. If user operations generate an oil mist, use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below the recommended mineral oil mist exposure limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Bright Yellow Brown	Pour Point: < 77 °F (- 25 °C)
Odor: Petroleum - mild	Solubility in Water: Negligible in water
Physical State: Liquid	Vapor Pressure: NA
Boiling Point: NA	Vapor Density (air=1): NA
Melting Point: NA	pH: NA
Specific Gravity: < 1	Viscosity @ 100 °C: 7.0 – 12.0 cSt

10. STABILITY AND REACTIVITY INFORMATION

Chemical Stability: Stable

Condition to Avoid: High heat and open flames

Incompatibility With Other Materials: May react with strong acids or strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.

Hazardous Decomposition Products: None known (None expected)

Hazardous Polymerization: Hazardous polymerization will not occur.

11. TOXICOLOGICAL INFORMATION

Primary Eye Irritation: NA

Primary Skin Irritation: NA

Acute Dermal Toxicity: NA

Subacute Dermal Toxicity: NA

Dermal Sensitization: NA

Inhalation Toxicity: NA

Oral Toxicity: NA

Mutagenicity: NA

Carcinogenicity: The International Agency for Research on Cancer (IARC) has concluded that there is inadequate data to evaluate the carcinogenicity to experimental animals of this class of product. IARC has concluded there is sufficient evidence that used gasoline-engine motor oils produce skin tumors in experimental animals. Also, IARC has determined this class of products belongs to Group 3 – “not classifiable as to its carcinogenicity to humans” .

Reproductive and Developmental Toxicity: NA

Teratogenicity: NA



MATERIAL SAFETY DATA SHEET
100% SYNTHETIC 2-STROKE MOTOR OIL
MOTORCYCLE / SNOWMOBILE / OUTBOARD MOTOR / ENGINE

Page 5 of 7

Immunotoxicity: NA

Neurotoxicity: NA

12. ECOLOGICAL INFORMATION

Ecotoxicity: The toxicity of this material to aquatic organisms has not been evaluated. Consequently, this material should be kept out of sewage and drainage systems and all bodies of water.

Environmental Fate: This material is not expected to be readily biodegradable.

13. DISPOSAL INFORMATION

Regulatory Information: All disposals must comply with federal, state, and local regulations. The material, if spilled or discarded, may be a regulated waste. Refer to state and local regulations. Department of Transportation (DOT) regulations may apply for transporting this material when spilled

Waste Disposal Methods: Waste material may be land filled or incinerated at an approved facility. Materials should be recycled if possible.

14. TRANSPORTATION INFORMATION

U.S. Department of Transportation (DOT)

Highway / Rail (Bulk): Not Regulated

Highway / Rail (Non-Bulk): Not Regulated

The DOT description is provided to assist in the proper shipping classification of this product and may not be suitable for all shipping descriptions.

International Information

Vessel: IMDG Not Regulated

Air: ICAO Not Regulated

15. REGULATORY INFORMATION

Regulatory Lists Searched: The components listed in Section 2 of this MSDS were compared to substances that appear on the following regulatory lists. Each list is numerically identified. See Regulatory Search Results below.

Health & Safety: 10 – IARC carcinogen, 11 – NTP carcinogen, 12 – OSHA carcinogen, 15 – ACGIH TLV, 16 – OSHA PEL, 17 – NIOSH exposure limit, 20 – US DOT Appendix A, Hazardous substances, 22 – FDA 21 CFR Total food additives, 23 – NFPA 49 or 325 .

Environmental: 30 – CAA 1990 Hazardous air pollutants, 31 – CAA Ozone depletors, 33 – CAA HON rule, 34 – CAA Toxic substance for accidental release prevention, 35 – CAA Volatile organic compounds (VOC's) in SOCOMI, 41 – CERCLA / SARA Section 302 extremely hazardous substances, 42 – CERCLA / SARA Section 313 emissions reporting, 43 – CWA Hazardous substances, 44 – CWA



MATERIAL SAFETY DATA SHEET
100% SYNTHETIC 2-STROKE MOTOR OIL
MOTORCYCLE / SNOWMOBILE / OUTBOARD MOTOR / ENGINE

Page 6 of 7

Priority pollutants, 45 – CWA Toxic pollutants, 46 – EPA Proposed test rule for hazardous air pollutants, 47 – RCRA Basis for listing – Appendix VII, 48 – RCRA waste, 49 – SDWA – (S)MCLs.

International: 50 – Canada – WHMIS Classification of substance, 54 – Mexico – Drinking water – ecological criteria, 55 – Mexico – Wastewater discharges, 56 – US – TSCA Section (12)(b) – export notification .

State Lists: 60 – CA – Proposition 65, 61 – FL – Substances, 62 – MI – Critical materials, 63 – MA – RTK, 64 – MA – Extraordinarily hazardous substances, 65 – MN – Hazardous substances, 66 – PA – RTK, 67 – NJ – RTK, 68 – NJ – Environmental hazardous substances, 69 – NJ – Special hazardous substances .

Inventories: 80 – Canada – Domestic substances, 81 – European – EINECS, 82 – Japan – ENCS, 83 – Korea – Existing and evaluated chemical substances, 84 – US – TSCA, 85 – China Inventory .

Regulatory Search Results: No components appear on any of the regulatory lists searched .

U.S. TSCA Inventory: All components of this material are on the US TSCA Inventory.

SARA Section 313: This product is not known to contain any SARA, Title III, Section 313 Reportable Chemicals at or greater than 1.0% (0.1% for carcinogens).

IARC: NA

SARA 311 / 312 Categories: Not Regulated

Canadian WHMIS Classification: Not a controlled substance under WHMIS

European Union Classification

Hazard Symbols: No classification recommended

Risk Phrases: No classification recommended

Safety Phrases: No classification recommended

16. OTHER INFORMATION

HMIS RATINGS: Health: 1 Flammability: 1 Reactivity: 0

(0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme, PPE:- Personal Protection Equipment Index recommendation, *- Chronic Effect Indicator). These values are obtained using the guidelines or published evaluations prepared by the National Fire Protection Association (NFPA) or the National Paint and Coating Association (for HMIS ratings).

Health and Environmental Label Language

CAUTION: Contains Petroleum Lubricant. Repeated skin contact can cause skin disorders.

ATTENTION: Used motor oil is a possible skin cancer hazard based on animal data. Repeated exposure to oil mist in excess of the OSHA limit (5mg/m³) can result in accumulation of oil droplets in pulmonary tissue.

PRECAUTIONARY MEASURES: Avoid excessive & prolonged skin contact. Wash thoroughly after handling. Avoid generation and inhalation of oil mists.



MATERIAL SAFETY DATA SHEET

100% SYNTHETIC 2-STROKE MOTOR OIL

MOTORCYCLE / SNOWMOBILE / OUTBOARD MOTOR / ENGINE

INSTRUCTIONS IN CASE OF FIRE OR SPILL: In case of fire, use water spray, foam, dry chemical or carbon dioxide. Water spray may be ineffective, but can be used to cool containers. In case of spill, do not use water, soak up with absorbent material.

DON'T POLLUTE, CONSERVE RESOURCES, RETURN USED OIL TO COLLECTION CENTER

ABBREVIATIONS THAT MAY HAVE BEEN USED IN THIS DOCUMENT:

OSHA - Occupational Safety and Health Administration	TWA - Time Weighted Average
STEL - Short-term Exposure Limit	PEL - Permissible Exposure Limit
ACGIH - American Conference of Government Industrial Hygienists	CAS - Chemical Abstract Service Number
API - American Petroleum Institute	IMO/IMDG - International Maritime Dangerous Goods Code
DOT - Department of Transportation (USA)	MSDS - Material Safety Data Sheet
IARC - International Agency for Research on Cancer	NFPA - National Fire Protection Association (USA)
TLV - Threshold Limit Value	NTP - National Toxicology Program (USA)
HMIS -Hazardous Materials Identification System	WHMIS -Workplace Hazardous Materials Information System
NIOSH-National Institute for Occupational Safety and Health	TSCA-Toxic Substances Control Act

Prepared by:

TEXAS TEA LUBES

425 N. Lake Blvd.#7/PO Box 1911

Tahoe City, CA 96145, U.S.A

Disclaimer of Warranty: The above information is based on the data of which we are aware and is believed to be correct as of the data hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modification of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.